

The RJ11 wall mount box series is a device used for connecting telephone lines. It simplifies the installation and maintenance of telephone systems.

Main Features

- Chemical resistance Corrosion Corrosion test is in compliance with IEC-60068-2-11



Application

- Communications, electronic countermeasures

Specification

Item	Parameter
Sockets and Box	ABS Flame Retardant Ivory
Case Color	Ivory
Weight	30g \pm 2g
Input & Output Treatment	Filled With Gel
Contact Pression (plug side)	4.5 - 5.5N/m ²
Insertion Force	20 - 50 N
Shock Resistance	55 - 64N/m ²
Free Drop Test	1.5m Height RJ.II Female 6P2C 50p Gold Plated Over Nickel Coating
Output Connector Type	RJ-11 Female 6P2C
RJ-II Contacts	50 μ Gold Plated Over Nickel Coating
Insulation Resistance	$\geq 1000M\Omega$
Dielectric Strength	DC 1000V or AC 700V/50Hz
High Current Holding	8/20 Wave (10KV)
Storage Temperature	-40 ~ 90° C
Atmospheric Pressure	70KPa ~ 106KPa
Operation Temperature	-30 ~ 80° C
Packaging	Bulk Carton
For Round Cable	3.05mm
Fire Risk	UL94V-0